F/A-18C "Hornet" Start-Up Procedure

F/A-18 Start-up Checklist	Quick Start-up
Set BATT to ON	**RH**
Set APU to ON	**L Arm**
Set ENG CRANK to R	**L Arm**
- R Eng RPM >25%	*LF*
R Eng to IDLE	**HOTAS**
- R Eng RPM = 60-65%	*LF*
Set DDI x2 to DAY / NIGHT	**LF/RF**
AMPCD brightness ON	**C**
HUD brightness ON	**C**
BLK LVL to ON	**C**
Set ALT to RDR	**C**
BLEED AIR rotate CW NORM to NORM	**RH**
Left DDI to HSI	**LF**
INS to GND / CV	**R Arm**
Select STD HDG	**L DDI**
Left DDI to FCS	**LF**
MASTER CAUTION x2 for FCS restack	**LF**
Select STOP *(on BIT FAILURES page)*	**R DDI**
Set ENG CRANK to L	**L Arm**
- L Eng RPM >25%	*LF*
L Eng to IDLE	**HOTAS**
- L Eng RPM = 60-65%	*LF*
Set OBOGS to ON	**L Arm**
Set HOOK BYPASS to FIELD / CARRIER	**LH**
Set FLAPS to HALF	**LH**
Set RADAR to OPR	**R Arm**
INS to IFA	**R Arm**
Set PITOT HEAT to ON	**L Arm**
Set L DDI to HUD	**L DDI**
Set R DDI to FCS	**R DDI**
- Wings unfolded (unless on CV)	*R DDI*
Uncage SAI	**RF**
Press ALR-67 PWR	**C**
Set ECM to STBY	**C**
Set DISPENSER to ON / BYPASS	**C**
Set other exterior lights as required	
Set LDG/TAXI LIGHT to ON	**LH**
Remove Wheel Chocks *(CV only)*	**COMMS**
Equip JHMCS or NVGs	**COMMS**
Disengage PARKING BRAKE	**LH**

Begin TAXI	Quick Start-up
CANOPY to CLOSE	**R Arm**
Lock SHOULDER HARNESS	**L ARM**
Arm EJECTION SEAT	**RH**
Press T/O TRIM	**L Arm**
- 12s and 30s on FCS	*R DDI*
After TAKEOFF	
Select IFF and press ON	**UFC**
Select D/L and press ON	**UFC**
Adjust AMPCD Gain / Cont / Sym	**AMPCD**
Set RDR ALT to 200ft / 80 ft *(Field or CV)*	**RH**
Set BINGO	**LF**
Select TIMEUFC	**AMPCD**
Select :ZTOD	**UFC**