

AGM-45 SHRIKE

AGM-45 TUNEUP (WRCS MODE)

GROUND CREW


- SELECT RF GUIDANCE KIT FOR TARGETED SAM SITES ► [SEE CHART]

PILOT

- SIGHT MODE ► [A/G]
- WRCS DELIVERY MODE ► [AGM-45]
- WEAPON SELECTOR ► [ARM]
- TGT/MSL REJECT ► [DF REJ]
- FLIGHT DIRECTOR ► [ON]
- STATION SELECT ► [SELECTED]
- MASTER ARM ► [ARM]

WSO

- ALT RANGE ► [TARGET ALT]
- RELEASE ADVANCE ► [SET IF RIPPLE FIRING]



AGM-45 EMPLOYMENT (WRCS MODE)

PILOT

- 1 CLIMB TO > 10,000 FEET AGL IF POSSIBLE
- 2 POINT NOSE IN DIRECTION OF EMITTER
- 3 CENTER NEEDLES ON ADI
- 4 ONCE WITHIN RANGE (10 MILES OR LESS)
PRESS AND HOLD BOMB RELEASE
- 5 FOLLOW INDEXER THROUGH ATTACK PROFILE
- 6 MISSILE WILL LAUNCH AUTOMATICALLY

INDEXER WRCS COMMANDS

- DIVE:** LOWER THE NOSE
- LEVEL:** MAINTAIN CURRENT STATE
- PULL-UP:** STEADY ROTATION BACK TO HORIZON OR LOW CLIMB

Shaded = Tracks with Tone, Unshaded = Tracks without Tone

RF KIT	SA-2	SA-3	SA-5	SA-6	SA-8	SA-10	SA-11	SA-15	SA-19	DE
Mk 22	TR			TR				STR		DE
Mk 23	TR		SR			TS,BB	STR		STR	
Mk 24.5	TR		SR			TS			STR	
Mk 24.34	TR		SR			TS				
Mk 25	TR			TR				STR		DE
Mk 36	TR	TR		TR		CS	STR			
Mk 37	SR	SR								
Mk 49.0	TR	TR		TR	TR	CS	STR			
Mk 49.1	TR	TR		TR	TR	CS	STR			
Mk 50	TR		SR			TS			STR	DE

TR=Track Radar|SR=Search Radar|BB=Big Bird|CS=Clam Shell|TS=Tin Shield|DE=Dog Ear